

The ADS_E 50/10 is a powerful servo amplifier for driving permanent magnet DC motors from 80 up to 500 watts.

Four modes can be selected by DIP switches on the board:

- Speed control using tacho signals
- Speed control using encoder signals
- IxR compensated speed control
- Torque or current control

The ADS_E 50/10 is protected against excess current, excess temperature and short circuit on the motor winding.

With the FET power transistors incorporated in the servoamplifier, an efficiency of up to 95% is achieved.

A built in motor choke combined with the high PWM frequency of 50 kHz allows the connection of motors with a very low inductivity. In most cases an external choke can be omitted.

Thanks to the wide input power supply range of 12 - 50 VDC, the ADS_E 50/10 is very versatile and can be used with various power supplies.

The Eurocard size allows the unit to be installed in a 19"-subrack or in a plug-in card system. Thanks to the controller circuit design, the ADS_E 50/10 is easily and quickly installed.



Table of Contents

1	Safety Instructions.....	2
2	Performance Data	3
3	Minimum External Wiring for Different Modes of Operation	4
4	Operating Instructions	5
5	Functions.....	7
6	Additional Possible Adjustments	10
7	Operating Status Display	12
8	Error Handling	13
9	EMC-compliant installation.....	13
10	Block Circuit Diagram.....	14
11	Pin Allocation Connector DIN 41612 Version H7/F24	14
12	Dimension Drawing	15
13	Accessories (not part of delivery).....	15

The latest edition of these operating instructions may be downloaded from the internet as a PDF-file under www.maxonmotor.com, category "Service & Downloads", Order number 168049.

1 Safety Instructions



Skilled Personnel

Installation and starting of the equipment shall only be performed by experienced, skilled personnel.



Statutory Regulations

The user must ensure that the servoamplifier and the components belonging to it are assembled and connected according to local statutory regulations.



Load Disconnected

For primary operation the motor should be free running, i.e. with the load disconnected.



Additional Safety Equipment

An electronic apparatus is not fail-safe in principle. Machines and apparatus must therefore be fitted with independent monitoring and safety equipment. If the equipment breaks down, if it is operated incorrectly, if the control unit breaks down or if the cables break, etc., it must be ensured, that the drive or the complete apparatus is kept in a safe operating mode.



Repairs

Repairs may be made by authorised personnel only or by the manufacturer. It is dangerous for the user to open the unit or make repairs to it.



Danger

Do ensure that during the installation of the ADS_E 50/10 no apparatus is connected to the electrical supply. After switching on, do not touch any live parts.



Maximum Supply Voltage

Make sure that the supply voltage is between 12 and 50 VDC. Voltages higher than 53 VDC or of wrong polarity will destroy the unit.



Short circuit and earth fault

The ADS_E 50/10 amplifier is not protected against winding short circuits against ground safety earth or Gnd!



Motor choke

The built in motor choke of the ADS_E 50/10 allows operation with almost all maxon DC motors with an output power higher than 80 watts. If necessary the motor continuous current must be slightly reduced.

Generally the following applies:

$$L_{\text{extern}} [mH] \geq \frac{V_{CC} [V]}{0.15 \left[\frac{1}{s} \right] \cdot I_D [mA]} - 0.15 [mH] - \frac{L_{\text{Motor}} [mH]}{3}$$

- Supply voltage V_{CC} [V]
- Nominal current (Max. continuous output current) I_D [mA]
- Terminal inductance L_{Motor} [mH]

Sought value:

- Additional required external inductance so that the continuous current only reduces by max. 10% as a result of warming.



Electrostatic Sensitive Device (ESD)

2 Performance Data

2.1 Electrical data

Supply voltage V_{CC} (Ripple < 5%).....	12 - 50 VDC
Max. output voltage	$0.9 \cdot V_{CC}$
Max. output current I_{max}	20 A
Continuous output current I_{cont}	10 A
Switching frequency.....	50 kHz
Max. Efficiency	95 %
Band width current controller	2.5 kHz
Built-in motor choke	75 μ H / 10 A

2.2 Inputs

Set value.....	-10 ... +10 V ($R_i = 20\text{ k}\Omega$)
Enable	+4 ... +50 VDC ($R_i = 15\text{ k}\Omega$)
Input voltage DC tacho "Tacho Input"	min. 2 VDC, max. 50 VDC ($R_i = 14\text{ k}\Omega$)
Encoder signals "Channel A, A \bar , B, B \bar "	max. 100 kHz, TTL level

2.3 Outputs

Current monitor "Monitor I" , short-circuit protected	-10 ... +10 VDC ($R_O = 100\ \Omega$)
Speed monitor "Monitor n" , short-circuit protected.....	-10 ... +10 VDC ($R_O = 100\ \Omega$)
Status reading "READY" Open collector.....	max. 30 VDC ($I_L \leq 20\text{ mA}$)

2.4 Voltage outputs

Aux. voltage, short-circuit protected	+12 VDC, -12 VDC, max. 12 mA ($R_0 = 1\text{ k}\Omega$)
Encoder supply voltage	+5 VDC, max. 80 mA

2.5 Trim potentiometers

IxR compensation
 Offset
 n_{max}
 I_{max}
 gain

2.6 LED indicator

Bi-colour LED	READY / ERROR
	green = READY, red = ERROR

2.7 Ambient temperature- / Humidity range

Operating.....	-10 ... +45°C
Storage.....	-40 ... +85°C
noncondensating	20 ... 80 %


2.8 Mechanical data

Weight	approx. 410 g
Dimensions.....	see dimension drawing, chapter 12

2.9 Terminal

Connector DIN 41612.....	Version H7/F24
--------------------------	----------------

3 Minimum External Wiring for Different Modes of Operation



4 Operating Instructions

4.1 Determine power supply requirements

You may make use of any available power supply, as long as it meets the minimal requirements spelled out below.
 During set up and adjustment phases, we recommend separating the motor mechanically from the machine to prevent damage due to uncontrolled motion.

Power supply requirements

Output voltage	V_{CC} min. 12 VDC; max. 50 VDC
Ripple	< 5 %
Output current	depending on load, continuous 10 A (short-time 20 A)

The required voltage can be calculated as follows:

Known values:

- ⇒ Operating torque M_B [mNm]
- ⇒ Operating speed n_B [rpm]
- ⇒ Nominal motor voltage U_N [Volt]
- ⇒ Motor no-load speed at U_N , n_0 [rpm]
- ⇒ Speed/torque gradient of the motor $\Delta n / \Delta M$ [rpm/mNm]

Sought values:

- ⇒ Supply voltage V_{CC} [Volt]

Solution:

$$V_{CC} = \frac{U_N}{n_0} \cdot \left(n_B + \frac{\Delta n}{\Delta M} \cdot M_B \right) \cdot \frac{1}{0.9} + 2 \text{ [V]}$$

Choose a power supply capable of supplying this calculated voltage under load. The formula takes into account a max. PWM cycle of 90 % and a 2 volt max. voltage drop.

Consider:

The power supply must be able to buffer the back-fed energy from brake operation e.g. in a condenser. With electronically stabilized power supply units it is to ensure, that the overcurrent protection responds in no operating condition.










4.2 Function of the potentiometers

	Potentiometer	Function	Turn to the	
			left ↶	right ↷
LED				
P1	P1	IxR	weak compensation	strong compensation
P2	P2	Offset	motor turns CCW	motor turns CW
P3	P3	n_{max}	speed slower	speed faster
P4	P4	I_{max}	lower min. 0.5 A	higher max. 20 A
P5	P5	gain	lower	higher
P6	P6	<ul style="list-style-type: none"> • For additional possible adjustments refer to chapter 6. • In use with the original frontplate, these potentiometers are covered! 		
P7	P7			
P8	P8			

4.3 Adjustment of the Potentiometers

4.3.1 Pre-adjustment

With the pre-adjustment, the potentiometers are set in a preferred position.
ADS_E units in original packing are already pre-adjusted.

 LED  P1  P2  P3  P4  P5  P6  P7  P8	Pre-adjustment			Adjustment: refer to section 4.3.2
	P1	I _{xR}	0 %	
	P2	Offset	50 %	
	P3	n _{max}	50 %	
	P4	I _{max}	50 %	
	P5	gain	10 %	
	P6	n _{gain}	25 %	
	P7	I _{gain}	40 %	
	P8	I _{cont}	50 %	Additional possible adjustments: refer to section 6.1/6.2

4.3.2 Adjustment

Encoder mode DC-Tacho mode I_{xR} compensation

- Adjust set value to maximum (e.g. 10 V) and turn potentiometer **P3** n_{max} so far that the required speed is achieved.
- Set potentiometer **P4** I_{max} to the limiting value desired.
Maximum current in the 0 ... 20 A range can be adjusted in linear fashion with potentiometer **P4**.
Important: The limiting value I_{max} should be below the nominal current (max. continuous current) as shown on the motor data sheet and may not exceed 10 A continuously.
- Increase potentiometer **P5** gain slowly until the amplification is set large enough.
Caution: If the motor vibrates or becomes loud, the amplification is adjusted too high.
- Adjust set value to 0 V, e.g. by short circuiting the set value input (link pins [b6] and [b8]). Then set the motor speed to 0 rpm with the potentiometer **P2** Offset.

In addition, only in the case of I_{xR} compensation:

- Slowly increase potentiometer **P1** I_{xR} until the compensation is set large enough so that in the case of high motor load the motor speed remains the same or decreases only slightly.
Caution: If the motor vibrates or becomes loud, the amplification is adjusted too high.

Current controller mode

- Set potentiometer **P4** I_{max} at the limiting value desired.
Maximum current in the 0 ... 20 A range can be adjusted in linear fashion with potentiometer **P4**.
Important: The limiting value I_{max} should be below the nominal current (max. continuous current) as shown in the motor data sheet and may not exceed 10 A continuously.
- Adjust set value to 0 V. Then set the motor current to 0 A with the potentiometer **P2** Offset.

Note:

- A set value in the -10 ... +10 V range is equal to a current range of approx. +I_{max} ... -I_{max}
- Configured as a current controller, **P1**, **P3** and **P5** are not activated.

5 Functions

5.1 Inputs

5.1.1 Set value

The set value input is wired as a differential amplifier.

Input voltage range	-10 ... +10 V
Input circuit	differential
Input resistance	20 kΩ (differential)
Positive set value	(+ set value [b6]) > (- set value [b8]) Negative motor voltage or current motor shaft turns CCW
Negative set value	(+ set value [b6]) < (- set value [b8]) Positive motor voltage or current motor shaft turns CW

5.1.2 Enable

If a voltage is given at "Enable", the servoamplifier switches the motor voltage to the winding connections. If the "Enable" input is not switched on or is connected to the Gnd, the power stage will be highly resistant and will be disabled.
The "Enable" input is short-circuit protected.

Enable	Minimum input voltage	+4.0 VDC
	Maximum input voltage	+50 VDC
	Input resistance	15 kΩ
	Switching time	typ 500 μs (by 5 V)
Disable	Minimum input voltage	0 VDC
	Maximum input voltage	+2.5 VDC
	Input resistance	15 kΩ
	Switching time	typ 100 μs (by 0 V)

5.1.3 DC Tacho

Minimum input voltage	2.0 V
Maximum input voltage	50 V
Input resistance	14 kΩ

Speed control range

The speed range is set using Potentiometer **P3** n_{\max} (max. speed at maximum set value).

For full speed control with ± 10 V, the tacho input voltage range must be at least ± 2 V.

Example for DC-Tacho with 0.52 V / 1000 rpm

2.0 V tacho voltage is equivalent to a speed of approx. 3850 rpm. If the full set value range has been used, the lowest adjustable speed with the n_{\max} potentiometer is 3850 rpm.

Lower speed ranges can be reached through a reduced set value range or by using a DC tacho with a higher output voltage, such as 5 V / 1000 rpm.

5.1.4 Encoder

Encoder supply voltage	+5 VDC max. 80 mA	
Maximum encoder frequency	DIP switch S5 ON:	10 kHz
	DIP switch S5 OFF:	100 kHz
Voltage value	TTL	
	low	max. 0.8 V
	high	min. 2.0 V

It is strongly recommended that the encoder be used with a built-in line driver. If the encoder is used **without** a line driver (without EncoderA\ and EncoderB\), speed breakdowns and max. speed limits must be expected because of the slower switching slope.

The servoamplifier does not need any home impulse I and I\.

5.2 Outputs

5.2.1 Current monitor “Monitor I”

The servoamplifier makes a current actual value available for monitoring purposes. The signal is proportional to the motor current. The “Monitor I” output is short-circuit protected.

Output voltage range	-10 ... +10 VDC
Output resistance	100 Ω
Gradient	approx. 0.4 V/A
positive voltage on current monitor output	corresponds to a negative motor current
negative voltage on current monitor output	corresponds to a positive motor current


5.2.2 Speed monitor “Monitor n”

The speed monitor is primarily intended for the qualitative estimation of the dynamics. The absolute speed is determined by the properties of the speed sensors and by the setting of the n_{\max} potentiometer. The output voltage of the speed monitor is proportional to the number of revolutions. The output voltage of the speed monitor is 10 V when the maximum number of revolutions set by the n_{\max} potentiometer has been reached. The “Monitor n” output is short-circuit protected.

Output voltage range	-10 ... +10 VDC		
Output resistance	100 Ω		
Example:	-10 V	corresponding speed	$-n_{\max}$ (CCW)
	0 V	corresponding speed	0 rpm
	+10 V	corresponding speed	$+n_{\max}$ (CW)

5.2.3 Status reading “Ready”

The “Ready” signal can be used to report the state of operational readiness or a fault condition on a master control unit. The “Open Collector” output is, in normal cases, i.e. no faults, switched to Gnd. In the case of a fault due to excess temperature or excess current, voltage processing error or too high encoder input frequency, the output transistor is not conducting (high resistance).






An external additional voltage is required:

Input voltage range	max. 30 VDC
Load current	$\leq 20 \text{ mA}$

Note:

The fault condition is stored. In order to reset the fault condition, the servoamplifier must be re-released (Enable). If the cause of the fault situation cannot be removed, the output transistor will immediately change to the not conducting state again.

6 Additional Possible Adjustments

Potentiometer			Function	Position	
				left ↶	right ↷
 P6	P6	n_{gain}	speed gain	low	high
 P7	P7	I_{gain}	current gain	low	high
 P8	P8	I_{cont}	continuous current limit	lower	higher

6.1 Adjustments potentiometer P6 n_{gain} and potentiometer P7 I_{gain}

In most applications, regulation setting is completely satisfactory using potentiometers **P1** to **P5**. In special cases the transient response can be optimized by setting the **P6** n_{gain} potentiometer. The **P7** I_{gain} potentiometer can, in addition, be adapted to the dynamics of the current regulator.

It is recommended that the success of changes to the settings of **P6** and **P7** be checked by measuring the transient response with an oscilloscope at the "Monitor n" and "Monitor I" outputs.



Pre-adjustment **P6** n_{gain} = 25 % and **P7** I_{gain} = 40 %.

6.2 Adjustments potentiometer P8 I_{cont} and current limit mode DIP switch S6

It is standard that a maximum current limiter is activated (DIP switch **S6** OFF). In this way the motor current is limited to the value set on potentiometer **P4** I_{max} (0.5 ... 20 A). If DIP switch **S6** is turned to ON, a cyclical current limiter is also activated. This current limiter method makes a certain level of motor protection against thermal overload possible.

For 0.1 seconds the motor current is limited to the value set on potentiometer **P4** I_{max} (0.5 ... 20 A) and then for 0.9 seconds current is limited to the value set on potentiometer **P8** I_{cont} (0.5 ... 20 A). After 1 second the cycle will repeat itself.

Pre-adjustment **P8** I_{cont} = 50 %; DIP switch **S6** = OFF



6.3 Maximal encoder frequency DIP switch S5

DIP switch **S5** permits selection of the maximum encoder input frequency.
A max. encoder frequency of 100 kHz is standard.

DIP switch S5 ON ↑		DIP switch S5 OFF ↓	
Max. Input frequency is 10 kHz		Max. Input frequency is 100 kHz	
Encoder pulse per turn	maximum motor speed	Encoder pulse per turn	maximum motor speed
16	37 500 rpm		
32	18 750 rpm		
64	9375 rpm		
128	4688 rpm	128	46 875 rpm
256	2344 rpm	256	23 438 rpm
500	1200 rpm	500	12 000 rpm
512	1172 rpm	512	11 719 rpm
1000	600 rpm	1000	6000 rpm
1024	586 rpm	1024	5859 rpm

Note:

To achieve good control characteristics, encoders with low impulse counts per turn should be run with the DIP switch **S5** ON ↑.

7 Operating Status Display




A bi-colour red/green LED shows the operating mode.

7.1 No LED

Reason:





- No supply voltage
- Fuse fault
- Wrong polarity of supply voltage
- Short circuit of the +5 V output

7.2 LED shines green

Blink pattern (green LED)	Operating Conditions
 LED on	Amplifier is activated (Enable)
	
	Disable function active

7.3 LED shines red

According to the blink pattern the following error messages can be identified:

Blink pattern (red LED)	Operating Conditions
① 	If the power stage temperature exceeds a limit of approx. 90°C, the power stage is switched off (disable status).
② 	If a motor current of more than approx. +/- 25 A is detected at the current actual value, the power stage will be switched off (disable status).
③ 	If the internal supply voltage cannot be set-up as expected the power amplifier is switched off (disable status).
④ 	If the input frequency at the encoder input is > 150 kHz, the power amplifier is switched off.

The fault condition is stored. In order to reset the fault condition, the servoamplifier must be re-released (Enable). If the cause of the fault condition cannot be eliminated, the error output will be disabled again immediately.

Reason:

- High ambient temperature (blink pattern ①)
- max. continuous current > 10 A (blink pattern ①)
- bad convection (blink pattern ①)
- Short circuit on the motor winding (blink pattern ②)

8 Error Handling

Defect	Possible source of defect	Measures
Shaft does not rotate	Supply voltage < 12 VDC	Check power plug pin [d22]
	Enable not activated	Check signal plug pin [b2]
	Set value is 0 V	Check signal plug pin [b6] and pin [b8]
	Current limit too low	Check adjustment potentiometer P4 I_{max}
	Wrong operational mode	Check DIP switch settings
	Bad contacts	Check wiring
	Wrong wiring	Check wiring
Speed is not controlled	Encoder mode: encoder signals	Check encoder signal
	DC- Tacho mode: tacho signals	Check pin [d6] and [d8] (polarity)
	IxR mode: compensation wrong	Check adjustment potentiometer P1 IxR

9 EMC-compliant installation

Power supply (+Vcc - Power Gnd)

- No shielding normally required.
- Star point-shaped wiring if several amplifiers are supplied by the same power supply.

Motor cable

- Shielded cable highly recommended.
- Connect shielding on both sides:
ADS_E 50/10 side: Terminal 3 "Ground Safety Earth" and/or bottom of housing.
Motor side: Motor housing or with motor housing mechanical design with low resistive connection.
- Use separate cable.

Encoder cable

- Although the ADS_E 50/10 can also be operated without a line driver, using an encoder with a line driver is recommended as this improves interference resistance.
- No shielding normally required.
- Use separate cable.

Analogue signals (Set value, Tacho, Monitor)

- No shielding normally required.
- Use cable shielding with analogue signals with small signal level and electromagnetically harsh environment.
- Normally connect shielding on both sides. Place shielding on one side if there are 50/60 Hz interference problems.


Digital signals (Enable, Ready)

- No shielding necessary.


See also block diagram in [chapter 10](#).

In practical terms, only the complete equipment, comprising all individual components (motor, amplifier, power supply unit, EMC filter, cabling etc.) can undergo an EMC test to ensure interference-free CE-approved operation.

10 Block Circuit Diagram




11 Pin Allocation Connector DIN 41612 Version H7/F24



12 Dimension Drawing

Dimensions in [mm]




13 Accessories (not part of delivery)

13.1 Front panel: Order number 168910


Dimensions in [mm]

natural-colored
anodised
on both sides
5 TE, 3 HE



13.2 Backplane with screw terminals: Order number 166873

Dimensions in [mm]



	No. of poles	Pitch	suitable for wire cross section
Encoder	6	3.81 mm	0.14 - 1.5 mm ² (single wire) 0.10 - 1.0 mm ² (multiple-stranded wire)
Signal	12	3.81 mm	0.14 - 1.5 mm ² (single wire) 0.10 - 1.0 mm ² (multiple-stranded wire)
Power	7	5.08 mm	0.14 - 1.5 mm ² (single wire) 0.14 - 1.5 mm ² (multiple-stranded wire)